

Packaged Terminal Air Conditioner for Replacement

# RSCC Series

Ice Air's RSCC Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

## Features:

- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



## RSCC Replaces:

Ice-Cap – RSCT  
 Ice Air – RSET

SERIES MODEL #	5RSCC07	5RSCC09	5RSCC13	8RSCC09	8RSCC13	8RSCC16	8RSCC18	7RSCC09	7RSCC13	7RSCC18
<b>Cooling Capacity (Btu/h)<sup>1</sup></b>	8,100	9,500	12,750	9,700	12,700	14,400	16,200	9,700	12,500	16,200
<b>EER</b>	9.5	8.9	8.3	8.85	8.3	8.3	7.75	8.85	8.3	7.75
<b>Heating Capacity - Hot Water (Btu/h)<sup>2</sup></b>	16,500	16,500	16,500	16,500	16,500	19,400	19,400	16,500	16,500	19,400
<b>Heating Capacity - Steam (Btu/h)<sup>3</sup></b>	18,700	18,700	18,700	18,700	18,700	20,000	20,000	18,700	18,700	20,000
<b>Electric Heating MAX (kW)</b>	1.5	1.5	1.5	4.3	4.3	4.3	4.3	3.5	3.5	3.5
<b>Voltage</b>	115	115	115	208	208	208	208	277	277	277
<b>Amperage</b>	7.4	9.3	13.4	5.3	7.4	8.3	10.0	4.0	5.4	7.5
<b>Watts</b>	853	1,067	1,536	1,096	1,530	1,735	2,090	1,096	1,506	2,090
<b>CFM Room Air High</b>	370	370	370	370	430	430	480	370	430	480
<b>CFM Room Air Low</b>	260	260	260	260	330	330	330	260	330	330
<b>CFM Outside Air (4)</b>	60	60	60	60	60	60	60	60	60	60
<b>CFM Extra Outside Air</b>	110	110	110	110	110	110	110	110	110	110
<b>Weight Net/ShipP</b>	113/129	117/133	124/138	117/133	124/138	132/148	141/157	117/133	124/138	141/157

## SPECIFICATION NOTES:

1. BTUH @ 80°F. DB/67 °F. WB INDOORS; 95 °F. DB OUTDOORS.
2. BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. FLOW RATE.
3. BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.

**IMPORTANT:** Accessories are optional. Deviations from standard accessories may affect performance; lower requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.