

Packaged Terminal Air Conditioner for Replacement

RSMK Series

Ice Air's RSMK Series Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

Features:

- Ultra-high efficiency – EERs to 9.1
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry


Replaces:

Singer – K, EK
 Remington – K, EK
 McQuay – K, EK, RK
 Ice-Cap – RSK/K, RSMK

SERIES MODEL #	5RSMK09	5RSMK13	8RSMK09	8RSMK13	8RSMK16	7RSMK09	7RSMK13
Cooling Capacity (Btu/h)¹	8,550	11,750	8,550	11,500	13,500	8,550	11,750
EER	9.1	8.4	9.1	8.5	8.05	9.1	8.4
Heating Capacity - Hot Water (Btu/h)²	16,500	16,500	16,500	16,500	19,400	16,500	16,500
Heating Capacity - Steam (Btu/h)³	18,700	18,700	18,700	18,700	20,000	18,700	18,700
Electric Heating MAX (kW)	1.5	1.5	1.5	4.3	4.3	3.5	3.5
Voltage	115	115	208/230	208/230	208/230	277	277
Amperage	8.2	12.2	4.5	6.5	8.1	3.4	5.0
Watts	940	1,399	940	1,353	1,677	940	1,399
CFM Room Air High	370	370	370	430	430	370	370
CFM Room Air Low	350	350	350	370	370	350	350

SPECIFICATION NOTES:

1. BTUH @ 80°F. DB/67 °F. WB INDOORS; 95 °F. DB OUTDOORS.
2. BTUH @ 200 °F. E.W.T.; 65 °F. E.A.T. & 2 G.P.M. FLOW RATE.
3. BTUH @ 2 PSIG STEAM & 65 °F. E.A.T.

IMPORTANT: Accessories are optional. Deviations from standard accessories may affect performance; louver requires 70% free area per original OEM specification; room enclosures must provide sufficient return air, free flowing supply air and must be properly sealed to prevent air recirculation; any non-standard components or accessories must be reviewed and approved by Ice Air or approved distributor.